

4 Megapixel Compact Fisheye Network Camera



Specification

Camera	
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	Color: 0.01lux @(F1.2, AGC ON) B/W: 0.001lux @(F1.2, AGC ON) 0 lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Lens	1.6mm, F1.6 Angle of view: 180°(horizontal), 112°(vertical)
Lens Mount	M12
Day & Night	Electronic
Compression Standard	
Video Compression	H.264/MJPEG
H.264 Type	Baseline Profile / Main Profile
Video Bit Rate	32 Kbps – 8 Mbps
Image	
Max. Resolution	2560 x 1520
Frame Rate	50Hz: 12.5fps (2560 x 1520), 25fps(1920×1080, 1280×960) 60Hz: 15fps (2560 x 1520), 30fps(1920×1080, 1280×960)
Digital Noise Reduction	3D DNR
Image Setting	Saturation, Brightness, Contrast , Hue, Sharpness, AGC, White Balance
Day/Night Switch	Auto/ Scheduled/ Alarm Trigger
Network	

Network Storage	NAS (Support NFS,SMB/CIFS)
Alarm Trigger	Line Crossing, Intrusion detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect, IP address conflict, Storage exception
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour
Security	User Authentication, Watermark, IP address filtering, Anonymous access
Standard	ONVIF, PSIA, CGI, ISAPI
Interface	
Communication Interface	1 RJ45 10M/100M Ethernet interface 1 RS485 interface(-S)
On-board storage	Built-in Micro SD/SDHC/SDXC slot, up to 64 GB
General	
Operating Conditions	-10 °C – 40 °C (14 °F – 104 °F) Humidity 95% or less (non-condensing)
Power Supply	12 VDC ± 10% / PoE (802.3af)
Power Consumption	Max. 6W
Dimensions	ø119.9 x 41.2
Weight	600g

Dimensions

